

5 Lever BS 3621:2007 Mortice Deadlock

2100S

Application:

- For timber doors hinged on the left or right
- Keys suitable for doors up to 54mm thick

Operation:

- Deadbolt locked or unlocked by the key from either side
- 20mm deadbolt for secure positive deadlocking and additional resistance against attack
- 2100S can be keyed alike with 2200S

Features:

- Anti-pick, anti-saw and anti-drill security features for resistance against attack
- Chamfered bolt design increases the performance of the lock under side load testing. The chamfer of the bolt also makes drilling attack more difficult
- Supplied with covered escutcheon to match forend

Benefits:

- Radius inner forend for ease of installation
- Can be installed into many UK mortices without the need for additional carpentry or spoiling the edge of the door
- Anti-pick and keyhole protection prevents forced entry by picking
- Hardened steel pins provide resistance to attack from sawing

Specification:

Reference	2100S (BS 20mm extended throw)
Case Size	68mm (2.5") or 81mm (3")
Backset	45mm or 57mm
Case	Steel, red powder coat
Forend	Stainless steel or brass finish
Striking Plate	Finished to match forend
Face Plate	Supplied with square faceplate which covers a radius inner forend
Deadbolt	With hardened steel rollers
Latch Bolt	n/a
Follower	n/a
Rebate Kit	2100REB 13mm (0.5") or 26mm (1")
Keying Groups	Supplied to differ or to pass/keyed alike. Supplied with 2 steel nickel plated keys
Key Blank Number	KB430

NB: Not suitable for master keying**Packaging:**

- Individually boxed, supplied in outer boxes of 10

Finishes:

- SC - Satin Stainless Steel forend and satin chrome finish box strike
- PL - Satin Brass finish forend and box strike

Standards:

- Tested to BS3621:2007

2 H 4 1 0 F 7 K D 0 B



- EN 1634-1 assessed for use on 60 minutes timber fire doors

Ordering Code Example:

J 2100S - PL - 2.50

(Boxed - Product Code - Finish - Case Size)

J 2100REB - 0.5 - PL

(Boxed - Product Code - Rebate Size - Finish)

