

5 Lever BS 3621:2007 Deadlock

2134E

Application:

- For timber doors hinged on the left or right
- Keys are suitable for doors up to 54mm thick

Operation:

- Deadbolt locked or unlocked by key from either side
- Extended 20mm deadbolt for secure positive deadlocking and additional resistance against attack
- 2134E can be keyed alike with 2234E

Specification:

Reference	2134E (BS 20mm extended throw)
Case Size	67mm (2.5") or 79.5mm (3")
Backset	45mm or 57.5mm
Case	Steel, red powder coat
Forend	Stainless steel or brass
Striking Plate	Finished to match forend
Deadbolt	Brass, with hardened steel rollers
Latch Bolt	n/a
Follower	n/a
Rebate Kit	2954 (13mm, 19mm or 25mm)
Keying Groups	May be supplied to pass or differ. Supplied with 3 steel nickel plated keys
Key Blank Number	KB430

NB: Not suitable for master keying

Features:

- Security box striking plate
- Anti-pick and anti-saw security features
- Available with square forend and locking plate
- 20mm bolt throw



Finishes:

- SC - Satin Chrome finish
- PL - Brass finish

Standards:

- Tested to BS3621:2007

2H410F7KD0V



- EN 1634-1 assessed for use on 60 minutes timber fire doors



- EC Certificate number: 0832-CPD-6038

Ordering Code Example:

J 2134E - PL - 2.50

(Boxed - Product Code - Finish - Case Size)

Y 2134E - PL - 2.50

(Visi Packed - Product Code - Finish - Case Size)

